



POLI-TACK 854

Product Information

Transparent Polyester film coated with a cross-linked acrylic adhesive offering excellent temperature resistance, ageing and UV stability.

The adhesive can be removed without residue even after long periods of usage.

POLI-TACK 854 transfer film is suitable for thermal transfer of heat sealing substrates, i.e. for the transfer of Flock- and Flex-film onto textiles.

Technical Data

| | | |
|------------------|----------------------------|----------|
| Carrier: | PET-film, transparent | |
| Adhesive: | Acrylic | |
| Adhesion [N/cm]: | 0,60 | +/- 10 % |
| Thickness [mm]: | 0,12 | +/- 5 % |
| Liner: | Siliconised PP film, white | |

Standard Dimensions

- 500 mm x 10 m
- 500 mm x 25 m
- 1.000 mm x 25 m
- 1.524 mm x 25 m

*Non-standard dimension. Converted after order entry. Extended delivery times may occur

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 2642 – 98 36 0
Fax: +49 2642 – 98 36 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

25/05/2018

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.